

## CounterTop

EFT930S<sub>series</sub>

Delivering the flexibility of a choice of rapid communication technologies with 32-bit ARM processing and cutting edge security, the Ingenico EFT930S series assures ultra fast yet highly cost-effective transactions – including debit, credit, reward and loyalty – that meet the needs of even the most demanding retail or banking environment. The EFT930S family's compact and space-saving design is packed with features – including integral smart card and long-swipe magnetic card readers, an ultra-fast ultra-quiet easy load printer, and backlit ergonomic keyboard – that combine to deliver intuitive and trouble free operations in any circumstance. This flexible and adaptable family offers a wealth of connectivity choice when it comes to communication. From POS integration, through to the peerless communication flexibility afforded by the EFT930S-EM and EFT930S-GEM combined-connectivity models, you're assured of the right solution for your business.

**ingenico**

# EFT930S series

## Security

The tamper resistant Ingenico EFT930S terminal series is universally EMV and PCI PED approved, delivering security-as-standard for consumer and merchant alike. A 32-bit RISC crypto-processor provides a uniquely scaleable and high-performance platform to support a host of new generation security applications, with no impact on transaction speed or reliability.

## Performance

Utilizing ARM9 and ARM7 microprocessor technology, the robust yet powerful ET930S range of countertop terminals combine innovation and performance with multiple connectivity options – assuring a faster, more convenient and more reliable transaction every time.

## Design/Ergonomics

Light enough to hand over for PIN entry, yet trim enough for even the smallest counter space, these neatly put together multi-application terminals are both versatile and user friendly. Clear white graphic displays, an easy to navigate keypad, and a high performance easy-load printer all add up to spectacular ‘zero delay’ customer service.

## Communication

The EFT930S – which delivers serial link POS integration via a Magic Box – and EFT930L are both equipped with a V32bis modem for fast EMV authorization. Boost your connectivity with our dual-communication models; the EFT930S-EM offers dual Ethernet and fast modem anytime, the fully loaded EFT930S-GEM unites GPRS wireless, Ethernet and fast modem anywhere.

## Software development

Ingenico delivers incremental revenue today and future proofs the terminal investments of tomorrow. Uniquely, the EFT930S series is backwards compatible with all 800+ Ingenico services and applications, while providing the rapid development environment on which to build a compelling portfolio of targeted, new generation services.

## Field Services

To reduce total cost of ownership and enable banks and merchants to maximize their terminal investments, Ingenico provides a comprehensive range of terminal and software update and management services – both remotely and in the field. Fully certified professional and local language helpdesks operate in every territory to ensure Ingenico is on hand to support customers 24 hours a day, seven days a week, 365 days a year.



NAME		EFT930S-L	EFT930S	EFT930S-xxx
<b>Processor</b>	Type: ARM 9 & ARM 7	●	●	●
	Speed: 200 MIPS & 50 MIPS	●	●	●
<b>Memory (RAM/Flash)</b>	8MB/16MB	●		
	8MB or 16MB/16MB		●	●
<b>Removable Memory</b>	MMC/SD Card			optional
<b>Communication Mode</b>	Dial-up Modem	●	●	M
	Ethernet			E
	GPRS			G
<b>SAM</b>	1	●		●
	2		●	●
<b>Card readers</b>	Smart card	1	1	1
	Magstripe Track 1/2			●
	Track 1/2/3	●	●	●
<b>Display</b>	Graphic 128 x 64	●	●	●
	Backlit	●	●	●
	Yellow/Green	●	●	
	White			●
<b>Keyboard</b>	Number of keys	16	16	16
	Function/Navigation keys	6	6	6
	Backlit	●	●	●
<b>Buzzer</b>		●	●	●
<b>Thermal Printer</b>	Lines/second	18 lps	18 lps	18 lps
	RS232	2		
<b>Connections on terminal</b>	Mini USB Host		2	2
	Mini USB Slave		1	1
	Power supply connector	1	1	1
<b>Power Supply</b>	External Power supply: 100-240V 50-60 Hz	●	●	●
<b>Magic Box</b>			●	●
<b>Connections on Magic Box</b>	Power supply connector		1	1
	RS232		1	1
	Line in		1	1
	Phone out		1	
	Ethernet			1
<b>Size (in mm)</b>	Terminal: 79 x 180 x 65	●	●	●
	Paper Roll (width/Ø): 58/Ø40	●	●	●
<b>Weight (in gr)</b>	Terminal	410	410	410 to 460
	Lens	optional	optional	optional
	Printer cover flap	optional	optional	optional
<b>Customization</b>	Casing	optional	optional	optional
<b>Environment</b>	Operating temperature: +5°C to +45°C	●	●	●
	Storage temperature: -20°C to +55°C	●	●	●
	Relative humidity: 85% HR at +40°C	●	●	●
<b>PCI PED</b>	Online & offline	●	●	●

www.ingenico.com

