

The ultimate hybrid reader  
PIN Pad for EMV migration

# Ingenico 3380

## PIN Pad Range

- **Ingenico 3380** is a countertop PIN Pad with hybrid reader ideal for use in multi-lane retail and single point-of-sale environments.
- Thanks to its EMV Hybrid Reader, the transition to Chip&PIN becomes easy for the cardholder.
- Based on Ingenico's new 32 bit architecture and equipped with EMV level 2 kernel, it provides fast processing of powerful cryptographic algorithms. It offers a fast and easy way to adapt the existing point-of-sale systems to new EMV and PIN-entry standards.
- Ingenico 3380 has been designed to ensure user friendliness with its large graphic display, function keys, backlit keypad and hybrid reader.



**EMV**  
Fast transaction  
time



**USB/Ethernet**  
Power over  
Ethernet



**UNICAPT**  
Application  
compatibility



**HSC 32 bits**  
Secure module



**Remote  
downloading**



**PCI PED**  
On-line and  
off-line certified



**Hybrid Reader**  
Easy chip  
migration



beyond  
payment

# Ingenico 3380



Easy connection to Ingenico terminals  
or cash registers through RS232 or USB



Backlit keyboard  
and lateral keys for  
easy menu navigation



Hybrid card reader  
making the transition  
to Chip&PIN easy



Optional privacy shield  
for the highest security  
standards



Up to 3 Security Access  
Modules (SAMs)



Thanks to its "Power over Ethernet" port,  
i3380 can be connected to an Ethernet LAN,  
reducing installation costs.



**Groupe Ingenico**  
192, avenue Charles de Gaulle - 92200 Neuilly-sur-Seine - France  
Tel. 33 (0)1 46 25 82 00 - Fax 33 (0)1 47 72 56 95  
www.ingenico.com

Your contact:

All rights reserved. This document is not binding and the specifications above  
can be modified without prior consent.

## Simple and cost effective transition to EMV

- Easy to use solution for retailers and cardholders transitioning to Chip&PIN: the hybrid reader means that the cardholder does not need to select either magnetic stripe or chip.
- Ingenico 3380 is compatible with the entire range of Ingenico countertop terminals (Amadeo, Banjo, i5100...).
- It offers a cost-effective way to upgrade existing point of sale and multilane retail cash registers to comply with new EMV and PIN entry standards.

## Ergonomic design

- The same PIN Pad can be connect to an ECR via either RS232 or USB, depending on the connector available on the ECR.
- Up to 3 Security Access Modules (SAMs).
- Secure downloading of new applications using local or remote download.
- The hybrid reader can read both magnetic stripe and smart cards, enabling the cardholder to use the same actions regardless of the technology of the card.
- i3380 uses the Power over Ethernet standard, reducing installation costs.
- The large graphic display gives clearly-presented data and commands. Its function keys permit a quick and simple way to access different applications.
- The optional privacy shield complies with all international security standards (ZKA, Interpay, BSK...).

## Physical and logical security

- The integrated High Security Core (HSC) has been developed from years of experience by the world leader in POS security, Ingenico. It offers different levels of security, meeting the most demanding requirements for payment transactions (PCI-Ped, ZKA, Interpay...). It has a 32-bit processor to support powerful encryption (RSA, DES, 3DES..), thus ensuring confidential data is secure.
- Multi application security is provided by UNICAPT technology permitting several applications to run independently on the same device. An additional benefit is the portability of previously written applications for Ingenico terminals.

<b>Memory</b>	1M SRAM + 4M Flash Memory 2M SRAM + 8M Flash Memory (option)
<b>Processor</b>	ARM 32 bits
<b>SAMs</b>	Up to 3 SIMs
<b>Security</b>	Integrated security. Ingenico's High Security Core
<b>Display</b>	Graphic, 128 x 64 pixels. Backlit
<b>Keypad</b>	15 keys. 2 + 2 lateral keys. Backlit
<b>Hybrid card reader</b>	ISO 1/2/3 EMV level 1 compliant. ISO 7816 1-1-3 Async/Sync. T=0 & T=1
<b>Connectivity</b>	RS232 + USB Ethernet (Power over Ethernet) Ethernet + RS232
<b>Environment</b>	0° to 40°
<b>Colour</b>	Grey