

# MICROS KWS4

## Keyboard Workstation Specs

Processor	<ul style="list-style-type: none"> <li>■ AMD Geode™ SC3200           <ul style="list-style-type: none"> <li>• Integrated system on chip with Geode™ core</li> </ul> </li> </ul>
Operating System	<ul style="list-style-type: none"> <li>■ Microsoft® Embedded Windows® CE .NET 4.2</li> </ul>
Solid State Flash Storage	<ul style="list-style-type: none"> <li>■ 32 MB Socketed Disk on Chip <i>(Expandable to 128 MB)</i></li> </ul>
Volatile Memory	<ul style="list-style-type: none"> <li>■ Up to 256 MB PC133 SDRAM <i>(Single DIMM Sockets)</i> 128 MB Standard</li> </ul>
Removable Flash Memory	<ul style="list-style-type: none"> <li>■ 64 MB Compact Flash - Standard 50 Pin Type 1 Compact Flash <i>(Expandable to 1 GB)</i></li> </ul>
Networking	<ul style="list-style-type: none"> <li>■ 10/100 BaseT on Board           <ul style="list-style-type: none"> <li>• Wake On LAN Supported</li> </ul> </li> </ul>
Operator Display	<ul style="list-style-type: none"> <li>■ Daylight Visible Transflective LCD           <ul style="list-style-type: none"> <li>• 240 x 64 Resolution</li> <li>• Gray Scale Display</li> </ul> </li> </ul>
Keyboard	<ul style="list-style-type: none"> <li>■ 108 keys</li> </ul>
Power Supply	<ul style="list-style-type: none"> <li>■ External, Universal Input / Auto-Switching</li> </ul>
Integrated Magnetic Stripe Reader	<ul style="list-style-type: none"> <li>■ 3 Track TTL Interface <i>(internal)</i></li> </ul>
Audio	<ul style="list-style-type: none"> <li>■ Internal PC Beeper</li> </ul>
Cash Drawer Ports	<ul style="list-style-type: none"> <li>■ 2 – MICROS Cash Drawer Ports</li> </ul>
Serial Port	<ul style="list-style-type: none"> <li>■ 1 – 9 pin RS-232 Serial Port</li> </ul>
Serial Port A	<ul style="list-style-type: none"> <li>■ 1 – RJ45 MICROS IDN RS422/RS485/RS232 Switchable Port</li> </ul>
Serial Port B	<ul style="list-style-type: none"> <li>■ 1 – RJ45 MICROS IDN RS422/RS485/RS232 Switchable Port</li> </ul>
Customer Display Port	<ul style="list-style-type: none"> <li>■ 1 – External 4 Pin Mini-DIN Connector</li> </ul>
USB Ports	<ul style="list-style-type: none"> <li>■ 2 – External USB</li> </ul>
Dimensions	<ul style="list-style-type: none"> <li>■ 13.7" W x 11.7" D x 5.4" T</li> </ul>
Weight	<ul style="list-style-type: none"> <li>■ Approximately 6.00lbs (2.7kg) / Shipping 9.5lbs (4.3kg)</li> </ul>
Enclosure	<ul style="list-style-type: none"> <li>■ Rugged ABS Plastic Blend, Spill Resistant Enclosure. <i>(MICROS Grey)</i> Passive Cooling <i>(No fans)</i></li> </ul>
Operating Temp	<ul style="list-style-type: none"> <li>■ -10° C to 60° C (14° F to 140° F)</li> </ul>
Certifications	<ul style="list-style-type: none"> <li>■ FCC Class A, UL, CE, TUV, CCC</li> </ul>



**micros**<sup>®</sup>