

MICROS KWS4

Keyboard Workstation Specs

Processor	<ul style="list-style-type: none"> ■ AMD Geode™ SC3200 <ul style="list-style-type: none"> • Integrated system on chip with Geode™ core
Operating System	■ Microsoft® Embedded Windows® CE .NET 4.2
Solid State Flash Storage	<ul style="list-style-type: none"> ■ 32 MB Socketed Disk on Chip <i>(Expandable to 128 MB)</i>
Volatile Memory	<ul style="list-style-type: none"> ■ Up to 256 MB PC133 SDRAM <i>(Single DIMM Sockets)</i> 128 MB Standard
Removable Flash Memory	<ul style="list-style-type: none"> ■ 64 MB Compact Flash - Standard 50 Pin Type 1 Compact Flash <i>(Expandable to 1 GB)</i>
Networking	<ul style="list-style-type: none"> ■ 10/100 BaseT on Board <ul style="list-style-type: none"> • Wake On LAN Supported
Operator Display	<ul style="list-style-type: none"> ■ Daylight Visible Transflective LCD <ul style="list-style-type: none"> • 240 x 64 Resolution • Gray Scale Display
Keyboard	■ 108 keys
Power Supply	■ External, Universal Input / Auto-Switching
Integrated Magnetic Stripe Reader	■ 3 Track TTL Interface <i>(internal)</i>
Audio	■ Internal PC Beeper
Cash Drawer Ports	■ 2 – MICROS Cash Drawer Ports
Serial Port	■ 1 – 9 pin RS-232 Serial Port
Serial Port A	■ 1 – RJ45 MICROS IDN RS422/RS485/RS232 Switchable Port
Serial Port B	■ 1 – RJ45 MICROS IDN RS422/RS485/RS232 Switchable Port
Customer Display Port	■ 1 – External 4 Pin Mini-DIN Connector
USB Ports	■ 2 – External USB
Dimensions	■ 13.7" W x 11.7" D x 5.4" T
Weight	■ Approximately 6.00lbs (2.7kg) / Shipping 9.5lbs (4.3kg)
Enclosure	■ Rugged ABS Plastic Blend, Spill Resistant Enclosure. <i>(MICROS Grey)</i> Passive Cooling <i>(No fans)</i>
Operating Temp	■ -10° C to 60° C (14° F to 140° F)
Certifications	■ FCC Class A, UL, CE, TUV, CCC



micros®