

# ALL YOU NEED IS SIMPLICITY

Designed for merchants with mid-low transaction volumes, the MagIC<sup>3</sup> C-series perfectly covers the essentials of electronic payment combining high security and compact design.

# MagIC<sup>3</sup> C-series

## The Power Of Simplicity

- The MagIC<sup>3</sup> C-series is the innovative solution for merchants looking for a device tailored for payment application.
- Its optimized connectivity reduces the cost of ownership by providing the perfect match between cost and functionality.

## Welcome To A MagIC<sup>3</sup> World

- Open&Sec platform, powered by two 32 bit-microprocessors, frees you to create applications making the most of the processing power at your disposal.
- With its Linux™ OS and USB connectivity, peripheral connection and application development on the MagIC<sup>3</sup> family have never been easier.
- The MagIC<sup>3</sup> C-series is the future proof plug-and-play solution.

## Superior Security For High Quality Standards

- Security is a major concern in any payment transaction. The MagIC<sup>3</sup> C-series was designed with all the expertise of the world leader in payment security and is fully compatible with the latest global security and communications standards such as EMV and PCI.
- The quality of MagIC<sup>3</sup> C-series assures the reliability and the robustness necessary to provide the best experience of electronic payment for acquirers, merchants and consumers.

## The Smart Solution

- The MagIC<sup>3</sup> C-series is compact, saving valuable counter space, easy to handle, simple to operate, and at the same time, ready for the future. It is the solution accessible to everyone that offers the best combination of essential payment functionality and optimized feature set.



### Dual 32-bit core architecture

- Main processor
- 32-bit ARM9 microprocessor
- 200 MHz
- Memory Management Unit
- Secure Processor
- 32-bit microprocessor

### Memory

- 4 MB flash, 16 MB SDRAM Display
- 128 x 64 pixel – Graphical Display

### Card readers

- Smartcard reader EMV 4.1 certified
- Bi-directional magnetic stripe reader
- ISO 1&2&3
- 1 SAM reader

### Communication

- Modem V32Bis
- USB 2.0

### Thermal printer

- Full graphical capabilities
- Easy loading
- 57 x 32 mm paper roll
- 8 lines/sec

### Security

- PCI PED Certified
- 3DES & RSA algorithms
- APACS CC EAL 4
- Master Session and DUKPT key management

### Physical

- Length: 179 mm
- Width: 85 mm
- Height: 65 mm
- Weight: 345 g

### RoHS compliant

- Operating temperature
- 0-45°C/32-115°F
- Relative humidity
- 90% maximum

### Power

- AC: 100-240V, 50/60 Hz
- DC: 7V, 3.4A

www.verifone.com

© 2011 VeriFone, Inc. All rights reserved. VeriFone, the VeriFone logo and MagIC<sup>3</sup> C-Series are either trademarks or registered trademarks of VeriFone in the United States and/or other countries. All other trademarks or brand names are the properties of their respective holders. All features and specifications are subject to change without notice. Reproduction or posting of this document without prior VeriFone approval is prohibited.  
01/11 45850 Rev A FS

 **VeriFone**  
THE WAY TO PAY™