

# THE LATEST GENERATION OF PAYMENT DEVICES

Pioneering the latest security standards, this architecture is the result of years of expertise in POS and the latest technology innovations. MagIC<sup>3</sup> X-series offers high-speed transactions as well as unrivaled flexibility of connection and communication without compromising security.

# MagIC<sup>3</sup> X-series

## Choose Top Security and Maximum Performance

- Security and speed are paramount to any transaction. This is why the X-series features Open&Sec technology.

## Navigate Like Your Mobile Phone

- User-friendliness was top of mind during the development of the X-series: compact design, icons, relevant shortcuts and animated pictures will make the use of menus simple and fast, like on a mobile phone.

## Welcome To A MagIC<sup>3</sup> World

- Open&Sec platform, powered by two 32 bit-microprocessors, frees you to create applications making the most of the processing power.
- With its Linux™ OS and USB connectivity, peripheral connection and application development on the MagIC<sup>3</sup> family have never been easier.
- The MagIC<sup>3</sup> X-series is the future proof plug-and-play solution.

## Simplify Your Life With A MagIC<sup>3</sup> Installation

- The device installation could not be simpler. The design has been optimized for efficient set-up and maintenance resulting in reduced total cost of ownership. Configuration can be stored on a USB key and downloaded in a matter of seconds.
- MagIC<sup>3</sup> X-series will give you peace of mind thanks to its level of quality and robustness.



### Dual 32-bit core architecture

Main processor  
32 bit ARM9 microprocessor  
200 MHz  
MMU  
Secure processor  
32 bit microprocessor

### Memory

8 MBytes flash, 16 Mbytes SDRAM

### Display

128 x 64 pixel graphical LCD  
with backlighting  
Icon bar

### Card readers

Smartcard reader EMV 4.0 certified  
Bi-directional magnetic stripe  
reader – ISO 1&2&3  
SAM readers: 4 SIM format  
3 SIM format+1Full (optional)

### Communications

X-5  
- Modem V32Bis  
- RS232  
- RS for PinPad  
- USB master

### X-8

- Modem V32Bis (optional V90)  
- RS232  
- RS for PinPad  
- 2 USB master  
- USB device  
- 10/100 Base-T Ethernet

### Thermal printer

Graphics capabilities  
Easy loading  
57 x 47 mm standard paper roll  
20 lines/sec

### Security

PCI certified  
PTS  
EAL4  
3DES and RSA algorithm  
M/S and DUKPT key management

### Physical

L x W x H: 212 x 93 x 78 mm  
Weight: 470 g

### Environmental

ROHS compliant  
Operating temperature:  
0-45°C/32-115°F  
Relative humidity 90% max

### Power

AC: 100-240V, 50/60 Hz  
DC: 7V, 3.4A

www.verifone.com

© 2011 VeriFone, Inc. All rights reserved. VeriFone, the VeriFone logo and MagIC<sup>3</sup> X-Series are either trademarks or registered trademarks of VeriFone in the United States and/or other countries. All other trademarks or brand names are the properties of their respective holders. All features and specifications are subject to change without notice. Reproduction or posting of this document without prior VeriFone approval is prohibited.  
01/11 45858 Rev A FS

 **VeriFone**  
THE WAY TO PAY™