



vivopay 4000™

Functional and Physical Integration of Contactless Payments into POS and ECR Systems

ViVOpay 4000 integrates physically into existing and new systems by a variety of mounting options.

The ViVOpay 4000 contactless payment device adapts easily to a wide variety of existing Point of Sale (POS) terminals and Electronic Cash Register (ECR) systems providing for physical and functional integration with the merchant system and check-out lane.

The small footprint (5" x 4.2" x 0.7") and flexible design of the ViVOpay 4000 was crafted to give merchants a variety of mounting options and provide for complete visual integration.



With ViVOpay 4000, merchants with digital signature pads and customer or clerk-facing POS or ECRs systems will be able to start accepting contactless cards and key fobs; generating 20% larger ticket value and a 20% shift from cash and checks*. ViVOpay 4000 is compatible with MasterCard® Paypass™, Expresspay™ from

American Express® and Visa® contactless

payment programs in addition to private-

label contactless gift and loyalty cards.



ViVOpay 4000 is compatible with all major contactless payment programs.



Benefits

- **Easy Integration:** Adapts to POS and ECR systems providing for physical and functional integration.
- **Revenue Increase:** Contactless payments generate ticket uplift and increased card usage.
- **Speed and Convenience:** Rapid check-out time during peak hours.
- **Low Cost:** Upgrading existing POS systems costs only a fraction of replacement for new contactless-enabled POS.

vivotech®
Quicker than cash, Safer than checksSM

(*) Transaction World Magazine "Contactless Payment Solutions - MasterCard PayPass" January, 2004 American Express "ExpressPay from American Express" Smart Card Alliance SmartTalk July, 2004

vivopay 4000™



The small footprint and flexible design of the Vivopay 4000 was crafted to give merchants a variety of mounting options and provide for complete visual integration to POS or ECRs systems.

Features

- **Contactless:** Accepts transactions from consumers using ISO/IEC 14443 Type A and B, NFC, Mifare Ultralight 15693 cards and key fobs.
- **Compatibility:** Works with most POS and ECR systems including Ingenico enTouch 1000, VeriFone Everest and OMNI 3750, HHP 3100, Hypercom Optimum series, @pos 3100, Partech ECR, Micros (Eclipse & Ultra), Radiant, and IBM SurePOS.
- **Speed:** Enables quick transactions improving store productivity and operational efficiencies:
- **Implementations:** Retail locations, ticket booths, multi-lane merchants, single-lane merchants, hospitality, car rental, and much more.
- **Consumer Intuitive:** Equipped with LEDs and sound to provide visual and audible cues to enable smooth and seamless transactions.
- **Flexible install:** Direct serial connection, Dynamic Strip™ and VIVOsmartcable™ technologies allow for flexibility when connecting to ECR and POS systems.
- **Secure:** Particular attention has been paid to provide a highly secure transaction whether financial, pre-paid, loyalty, or gift.
- **Intellectual Property:** Protected by several patent-pending applications.

* VIVOtech, VIVOfob, VIVOcard, VIVOpay, VIVOplatform are trademarks or registered trademarks of VIVOtech Corporation. All other trademarks or brand names are the properties of their respective holders. Features and specifications are subject to change without notice.

Domestic offices:

West Coast
VIVOtech
Corporate Headquarters
451 El Camino Real,
Santa Clara, CA 95050
Phone: (408) 248-7001

East Coast & Canada
40 East 94th Street #3C
New York, NY 10128
Phone: (212) 423-3065

International offices:

Singapore
152 Beach Road #02-08
Gateway East Singapore 189721
Phone: (65) 6334-9045

Japan
Shinagawa Intercity
Tower A, Level 28
2-15-1, Konan, Minato-ku
Tokyo 1086028 Japan
Phone: +81 3 6717 4223

Europe
54, Beechwood Av.
Ruislip, Middx, HA4 6EJ
United Kingdom
Phone: 44 1895 47 99 17

Specifications

Hardware

Contactless
Interface: 13.56 MHz
ISO 14443 Type A/B,
ISO 15693 Mifare®,
Ultralight, IR

Physical

Height: (Unfolded) 5 inches (125.0 mm)
(Folded) 2.5 inches (62.5 mm)
Width: (Widest) 4.2 inches (105 mm)
Depth: .7 inches (10 mm)

Environmental

Operating Temp.: 0 to 40 c (32 to 104 F)
Storage Temp.: -18 to 70 c (0 to 158 F)
Operating Humidity: 20% to 90% non-condensing

Power

Voltage: 120 VAC, 60 Hz (US)
220 VAC, 50 Hz (International)

vivotech®
Quicker than cash, Safer than checks™

www.vivotech.com
sales@vivotech.com