



# vivo<sup>pay</sup> Kiosk II

**Flexible Integration of Contactless Payments for Customer-Facing Self-Service Systems**

**2-Piece Modular ViVOpay Kiosk II Provides Easy Integration with Host Systems without Re-Certification**



The ViVOpay Kiosk II is a flexible stand-alone contactless reader comprised of a compact controller module and an RFID antenna module packaged individually giving equipment manufacturers flexibility to integrate contactless payment functionality with their host systems. The design approach allows the controller module to be easily installed within the cabinetry of a 3rd-party host system and the antenna to be installed with minimal footprint and effort in a customer-facing location.

The ViVOpay Kiosk II is certified with most contactless payment programs such as MSD-based MasterCard® PayPass™, ExpressPay from American ExpressSM, Visa® PayWave and Discover® Zip™ and capable of EMV-Based OneSmart® MasterCard® PayPass™ and Visa® payWave qVSDC. In most cases a host system with ViVOpay Kiosk II would be enabled with contactless payment functionality without the need to go through lengthy re-certification.

The ViVOpay Kiosk II also supports contactless ticketing functionality such as used in most transit systems worldwide as well as NFC mobile phone payments and promotions. It's powerful ARM processor and remote download capability allows for future scalability and updates. Operators can rest assured that the investment of today will support the developments in contactless payments of the future.

## Benefits

- **Flexible Integration:** 2-piece modular design allows easy integration Kiosks, Turnstiles and Ticketing Systems.
- **Contactless Payments Certified:** Host system doesn't need to go through lengthy re-certification.
- **Outdoor/ Indoor:** Weather-proof customer-facing antenna allows installation in outdoor devices.
- **Future-proof:** Application can easily be updated remotely.
- **Additional Applications:** Equipped with powerful ARM processor for advanced contactless functionality.



Antenna Module

*ViVOpay Kiosk II design approach allows controller module to be installed inside host system and antenna to be installed with minimal footprint in a customer-facing location.*



Controller Module



# vivo<sup>pay</sup> Kiosk II



## Features

- **Contactless:** Compatible with ISO/IEC 14443 Type A and B, NFC and MiFare®.
- **Applications:** Retail drive-thru, ticketing machines, transit turnstiles / fare collection systems, reload machines for transit systems, airport self check-in, parking ticket validation/payment boxes, parking meters and many other inside and outdoor applications.
- **Flexibility:** Controller module and RFID antenna module packaged individually give equipment manufacturers flexibility to integrate contactless payment functionality with their host systems.
- **Remote Download:** Post-deployment firmware updates via remote download without requiring additional hardware or device resetting.
- **Easy Integration:** RS232 connectivity combined with VIVOtech serial interface.
- **Speed:** Enables quick transactions improving vending machine-based sales.
- **Consumer Intuitive:** Equipped with LEDs and sound feedback to guide consumers through the payment process.
- **Secure:** Provides highly secure transaction whether financial, ticketing, pre-paid, loyalty, or gift.
- **Intellectual Property:** Protected by several patent-pending applications.

\* VIVOtech, VIVOfob, VIVOcard, VIVOpay and VIVOplatform are trademarks or registered trademarks of VIVOtech Corporation. All other trademarks or brand names are the properties of their respective holders. Features and specifications are subject to change without notice.



## Specifications

### Hardware

Processor:	ARM processor
Audio-Visual:	Beeper and LEDs
Input Power:	7.5-36VDC

### Contactless Transactions

Interface:	13.56MHz ISO 14443 Type A/Type B and MiFare
Payment Applications*:	American Express ExpressPay Discover Zip Mastercard <i>PayPass</i> Mstripe (M/Chip capable) Visa payWave MSD and (qVSDC capable) JCB/Jspeedy
Other Contactless Applications:	VIVOcard Pass-Through mode

### Connectivity

Interface:	Serial RS-232
Firmware upgrades:	Remote firmware download

### Physical Dimensions

Controller Module	
Height (X):	105 mm
Length (Y):	76.2 mm
Width (Z):	22.5 mm
Antenna Module	
Height (X):	70 mm
Length (Y):	60 mm
Width (Z):	17.2 mm

### Environmental

Operating Temp.:	-13F to +158F (-25C to +70C)
Storage Temp.:	-40F to +185F (-40C to +85C)
Operating Humidity:	10% to 90% non condensing
Other:	Weather-proofed UV-rated plastic enclosure

\*Specific product specification will depend on hardware and software configuration.

### Domestic offices:

**VIVOtech**  
**Corporate Headquarters**  
 451 El Camino Real,  
 Santa Clara, CA 95050  
 Phone: (408) 248-7001

### International offices:

**Singapore**  
 133 New Bridge Road  
 #08-10 Chinatown Point 89721  
 Singapore 059413  
 Phone: +65 6533 3974

**Japan**  
 Shinagawa Intercity  
 Tower A, Level 28  
 2-15-1, Konan, Minato-ku  
 Tokyo 1086028 Japan  
 Phone: +81 3 6717 4223

**Europe**  
 1 Birling Road  
 Tunbridge Wells  
 Kent TN2 5LX  
 United Kingdom  
 Phone: +44 870 803 2515



www.vivotech.com  
 sales@vivotech.com